

Christy[®] Pak Metal Pall Rings

FEATURES

- Available in a wide range of sizes, thicknesses and metallurgies
- High mechanical strength
- Economical
- High available surface area
- Well-proven in thousands of installations worldwide
- Higher hydraulic capacity than first generation metal random packings



PACKING DATA

Nominal Size		Thickness		*Density		Surface Area		Free Space
(in)	(mm)	inches	(mm)	lbs/ft ³	(kg/m ³)	ft ² /ft ³	(m ² /m ³)	(%)
1/4	(6)	0.012	(0.3)	56	(897)	276	(905)	89
3/8	(10)	0.012	(0.3)	30	(478)	147	(483)	94
5/8	(15)	0.012	(0.3)	24	(385)	110	(361)	95
1	(25)	0.012	(0.3)	14	(225)	66	(217)	95
1-1/2	(38)	0.016	(0.4)	13	(209)	41	(135)	96
2	(50)	0.02	(0.5)	12	(193)	32	(105)	97
3	(76)	0.03	(0.8)	12	(193)	24	(79)	98

* Density is based on 304SS and the following thicknesses: 1/4" and 1" - 0.3mm, 1 1/2" - 0.4mm, 2" - 0.5mm and 3" - 0.8mm.
Other wall thicknesses are available upon request.

Christy Catalytics, LLC offers a complete range of catalyst bed supports, tower packings and tower internals.